



Solvent based glue and tar remover

Product Description

Reno Flash is a liquid product for the efficient removal of tar and glue.

Properties

Reno Flash can be used for the bodywork of vehicles, tar machines, ships and the tar industry of cardboard and paper. Reno Flash is ready to use and is non corrosive.

Direction of use

Automobile sector:

- Spray Reno Flash on the tar spots, and wipe with a clean, dry cloth.

Trucks:

- Spray Reno Flash on the body work and rinse with a high pressure.

Sector of bridges and roads:

- Put Reno Flash in the drum and empty the solution in the tar pipes.

Avoid contact with sensitive plastics (such as: tail lights)!

Specifications

Physical state	Liquid
Colour	Colourless
Freezing point	-60 °C
Boiling point	155 - 185 °C
Flash point	> 38 °C
Relative density	ca 0.877
Solubility in water	< 0.1 %

Storage and Disposal

Store in tightly closed, properly ventilated containers away from heat, sparks, open flame. Keep in fireproof place. Dispose in a safe manner in accordance with local/national regulations. Avoid release to the environment. Dispose of this material and its container at hazardous or special waste collection point.

Safety instructions for the user

Keep out of reach of children. Care should be taken to reduce the possibility of eye contact.

In case of eye contact, rinse immediately with plenty of water. Obtain medical attention if pain, blinking, tears or redness persist. In case of inhalation, assure fresh air breathing. If you feel unwell, seek medical advice.

In case of skin contact, remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

In case of ingestion, rinse mouth. If swallowed, seek medical advice immediately and show this container or label.

Please check the MSDS.

Not all CID LINES products are available in all countries. For information about availability of a specific product, please contact your CID LINES dealer.

KENOTEK

Waterpoortstraat 2, 8900 Ieper (Belgium)
T +32 (0)57 21 78 77 • F +32 (0)57 21 78 79 • www.kenotek.eu

